



**OIL-ALERT®
Detectors**

Model Number	Buzzer Mounted in Unit	DPDT Isolated Relay Contacts	Works With Series 2100 Monitors	Batteries Required (Batt Operation)	Alarm Duration (Batt Operation)	Net Price Each	Feature Description
OA	X		1	3 days	\$375	Lowest cost detector • Provides loud on-off action buzzer when activated • Simple to install- snap in batteries and locate unit in potential danger area	
OA-5	X	X	2	3 days	\$475	Ideal for tie-in to existing alarm panel • Upon detection of liquid 1) Isolated relay contacts transfer and hold 2) loud on-off action buzzer activates • Relays rated 1 Amp @28VDC	
OA-2100	X		X	0	N/A	\$475	Used with SERIES 2100 monitors listed below. Provides audible alarm and pigtail leads for monitor connection • Powered by monitor.

There are three ways to provide power to Oil Alerts, 9v alkaline battery(s), PS-3 Power Supply and Voltage Module. OA-2100 is powered by the Series 2100 monitor.

SERIES 2100 monitors

SM-6	\$2,175	6 Channel monitor / power supply • Shelf mounted • Provides 2 SPDT isolated relay contacts • Audible and visual alarms • Rechargeable battery back-up.
SM-12	\$3,085	12 Channel monitor / power supply • Shelf mounted • Provides 2 SPDT isolated relay contacts • Audible and visual alarms • Rechargeable batter back-up.
WM-6	\$2,765	6 Channel monitor / power supply • Wall mounted • Provides 2 SPDT isolated relay contacts Audible and visual alarms • Rechargeable battery back-up.
WM-12	\$3,795	12 Channel monitor / power supply • Wall mounted • Provides 2 SPDT isolated relay contacts • Audible and visual alarms • Rechargeable battery back-up.

Wire and Cable

		500'ft.		1000'ft.	
		WT.		WT.	
Type "B"	Signal/Power wire - 2 conductor twisted pair, stranded #22 AWG. with vinyl jacket 0.165" O.D.. For use in Oil Alert to AD-6 signal or PS-3 power runs less than 500 ft..	\$110	10#	\$185	16#
Type "F"	Signal/Power wire - 3 conductor, shielded, stranded #22 AWG. with vinyl jacket 0.175" O.D.. For use in all Series 2100 Oil Alert systems.	\$250	13#	\$415	22#
#18 power	Power wire - 2 conductor twisted pair, stranded #18 AWG. with vinyl jacket 0.226" O.D.. For PS-3 power runs between 500'and 2500 ft..	\$235	12#	\$450	17#

Accessories / Options

9V Battery	\$3	Industrial type, non-rechargeable, 9V Alkaline battery.
Voltage Module	\$69	Eliminates the need for batteries • Module snaps into an Oil Alert in place of batteries. Accepts voltage of 12-24 Volts AC or DC from user power source to power Oil Alert. <i>Order one module per Oil Alert</i>
PS-3	\$465	Power supply with battery backup, powers up to 24 Oil Alerts • plugs into 120VAC. Includes rechargeable battery for backup
AD-6	\$1,250	Auto-Dialer and annunciator • Ideal for unmanned or remote site monitoring • Accepts Oil Alert or other alarm devices with relay contact outputs. • Plugs into 120VAC. • Includes rechargeable battery for backup. • For details see page 15 in Water Alert catalog
PR-WM	\$465	Used to control high powered equipment such as pumps, motors and solenoids from an OA-5 Detector. • Also provides power for up to 2 Oil Alert detectors. • Plugs into 120VAC.
RA-WM	\$365	Remote alarm panel, used for additional indication of oil leakage. Compatible with all Series 2100 monitors and OA-5 Oil Alert Detectors. • Plugs into 120VAC.
SM-2	\$85	2 pack of replacement Oil Alert sensing modules.

PREVIOUSLY MANUFACTURED PRODUCTS - This price list shows pricing for the latest line of Dorlen detectors and monitors. It is recommended these products be used for new installations. However, if you are expanding an existing installation and require any previously manufactured product these are available... Please request pricing on the specific product(s).


HOW TO ORDER

Orders may be placed by phone, fax, or mail (to below address) on your company order form. Please verify pricing if your price list is not the current year.

ALL PRICES:

FOB MILWAUKEE, WI
(Shipping prepaid and added to invoice)
Orders normally shipped UPS

Credit card orders accepted!



TERMS: Net 30, subject to credit approval.

NOTE: Instructions, Wiring Diagrams (if applicable) and Warranty included with all equipment shipped.

WARRANTY

All products are carefully manufactured, inspected and tested prior to shipment. Any defects in material or workmanship under normal use will be corrected at manufacturer's expense for a period of **Three years** on all Oil Alert detectors and **Five years** on all other equipment from date of purchase. This warranty is limited to repair or replacement of the unit or parts contained herein (not to include 9v Alkaline battery or internal 12v rechargeable battery). Since the manufacturer has no control on final use of this product, neither seller nor manufacturer shall be liable for any loss or damage, direct or consequential, arising from the use of this product. The above is in lieu of all other warranties, guarantees, statements expressed or implied.

Dorlen Products Inc.

6615 West Layton Avenue,

Milwaukee, WI 53220

Phone: 414-282-4840

Fax: 414-282-5670

E-Mail - Dorlen@Execpc.com

Web Site - www.Oil-Alert.com

www.WaterAlert.com



LEAK DETECTION SYSTEMS - SINCE 1975